



CPF18/5 Five Head - Moulder

STANDARD MACHINE INCLUDES:

- ◆ Service Spanners
- ◆ Instruction manual



TECHNICAL DATA:

Max. diameter of wood	7.07 x 4.72
Min. diameter of wood	0.63 x 0.24
Min length of wood	16.90
Max. stock removal	0.39 x 0.24
Length of entry table	66.81
Diameter of shafts	1 1/4
Diameter of cutterblock 1st Spindle	4.72
Min. Diameter of tooling spindle #2-#5	3.93
Max. Diameter of tooling spindle #2-#5	7.07
Spindle RPM Feed Speed	6000 RPM
Feeding speed	12-60 ft per minute
Diameter of feeding rollers	4.72
Suction dust hood diameter	4.72
Main motor power	1@10 hp, 3@7.5 hp
Feeding motor power	2 hp
Noise level with technology LpAeq	100.7 dB (A)

OPTIONS (Ordered with Machine):

- Overhead Electrical Control Panel (includes Upper suction Hood listed below)
- Digital indication of rip fence
- Three-phase braking motor, 9 HP, 60Hz
- Single-phase braking motor, 3.6 HP, 60Hz



Tech Mark, Inc.
7901 Industry Drive
North Little Rock, AR 72117
PH: 501-945-9393 Fax: 501-945-0312
Website: www.rojekusa.com - or - www.tech-mark.com