



June 1, 2004

# PF 300L 12" Panel Saw with 102" 118" or 126" Aluminum Sliding Table

## STANDARD MACHINE INCLUDES:

- ◆ 102" CV3 "format" sliding table and outrigger
- ◆ Three-phase, 6.5 HP motor, 60 Hz
- ◆ Scoring unit with separate motor
- ◆ Cut up to 1<sup>3</sup>/<sub>16</sub>" dado (w/insert)
- ◆ Upgrade Rip fence with micro-adjustment
- ◆ CV3 sliding table angle fence
- ◆ 59" rip table extension
- ◆ Sliding table stop bar
- ◆ Straight-line rip stop
- ◆ Outrigger roller
- ◆ Outrigger aluminum extension
- ◆ Overload protection
- ◆ UL Standard
- ◆ Service spanners
- ◆ Instruction Handbook



\* Shown with optional Overhead Electrical Control Panel, and Upper Suction Hood/Saw Guard.

### TECHNICAL DATA:

Max. diameter of main saw blade	12"
Working table size	19 5/8" x 46 5/8"
<b>Sliding Table size</b>	<b>11 1/4" x 102" 118" or 126"</b>
Main saw arbor	1"
Blade tilting	0° - 45°
Max. cut height at 90°	4"
Max. cut height at 45°	2 3/4"
Speed of main/scoring blade	4352/8530 RPM
Scoring blade arbor	20mm
Scoring saw blade dia.	100mm
Rip Capacity	59"
<b>Cross-cut capacity</b>	<b>102" 118" or 126"</b>
Suction dust hood dia.	4"
Scoring Motor	3/4 HP (0.5 kw)
Electrical	230V, 3Ø
Net weight	1,325 lbs.

### OPTIONS (Ordered with Machine):

- Overhead Electrical Control Panel (includes Upper suction Hood listed below)
- Digital indication of rip fence
- Three-phase braking motor, 9 HP, 60Hz
- Single-phase braking motor, 3.6 HP, 60Hz

### OPTIONS/ACCESSORIES (Available Anytime):

- Upper suction hood / saw guard
- Split scoring blade 100mm (4")
- Carbide saw blade 300mm (12")



Tech Mark, Inc.  
 7901 Industry Drive  
 North Little Rock, AR 72117  
 PH: 501-945-9393 Fax: 501-945-0312  
 Website: [www.rojekusa.com](http://www.rojekusa.com) - or - [www.tech-mark.com](http://www.tech-mark.com)